

HYVAC PRODUCTS, INC.

P.O. Box 389 Phoenixville, Pa 19460 Ph 610-792-0500 Fax 610-792-0600

MATERIAL SAFETY DATA SHEET

Prepared 01/02/2005

This Product Safety information is provided periodically to assist our customers in assessing compliance with Health/Safety/Environmental Regulations. Please forward this to your manager of Safety and Health.

SECTION I. IDENTIFICATION

TRADE NAME: HyVac Flushing Oil
CATALOG NUMBER: 93060
SYNONYMS: Flushing Oil
CAS REGISTRY NUMBER: 64741-88-4
UN NUMBER:
TECHNICAL CONTACT: (610) 792-0500
MATERIAL HAZARD EVALUATION (Per OSHA's Hazard Communication Standard 29 CFR Part 1910.100) (OHCS).

HEALTH: Non-Hazardous. (OHCS)
PRECAUTIONARY STATEMENT: None

SECTION II. GENERIC COMPOSITION / COMPONENTS

<u>COMPONENTS</u>	<u>CAS #</u>	<u>%</u>	<u>HAZARD DATA</u>
Refined Petroleum Oil(s)	64741-88-4	100	Oral: LD50(rat): >15g/kg Eye: Practically Non-Irritating Skin: Practically Non-Irritating Ihln: LC50/4H(rat): >5,000mg/m ³

SECTION III. PHYSICAL DATA

Physical Hazard Classification (Per 29 CFR Part 1910.1200)

BOILING POINT:	760 mmHg	Wide Range °F
MELTING POINT:	°C - °F	NA
SPECIFIC GRAVITY:	(H ₂ O=1)	0.87
VAPOR PRESSURE:	mmHg (20°C)	Below .0001
VAPOR DENSITY:	(Air=1)	14
SOLUBILITY:	in H ₂ O, % by Wt.	Negligible
EVAPORATION RATE:	(ethyl ether = 1)	1000 times slower
% VOLATILES:	by Volume	Negligible
PH OF UNDILUTED PRODUCT:		ND
APPEARANCE:		Light Amber liquid
ODOR:		Little odor

<u>No</u>	Combustible	<u>No</u>	Oxidizer	<u>No</u>	Pyrophoric
<u>No</u>	Compressed Gas	<u>No</u>	Reactivity	<u>Yes</u>	Stable
<u>No</u>	Explosive	<u>No</u>	Organic Peroxide	<u>No</u>	Unstable
<u>No</u>	Flammable				

SECTION IV. FIRE AND EXPLOSION DATA

FLASH POINT, COC	215°C - 420°F	NEFA☼	
FLASH POINT, PM	211°C - 412°F	HEALTH:	1
FIRE POINT, COC	245°C - 475°F	FLAMMABILITY:	1
		REACTIVITY:	0

FLAMMABLE LIMITS IN AIR, % VOL.:

Lower: ND

Upper: ND

EXTINGUISHING MEDIA: CO₂, Dry chemical, Foam or Water Fog.

SPECIAL FIRE FIGHTING PROCEDURE: Wear self-contained breathing gear when fire fighting in confined spaces.

UNUSUAL FIRE OR EXPLOSION HAZARD: Water may cause frothing.

HyVac® assignment based on our evaluation per NFPA guidelines.

Hazard Rating: Least - 0 Slight - 1 Moderate - 2 High - 3 Extreme - 4

SECTION V. REACTIVITY DATE

STABILITY: Stable - Yes Unstable - No

CONDITIONS CONTRIBUTING TO INSTABILITY: None
INCOMPATIBILITY: Strong Oxidants

HAZARDOUS DECOMPOSITION PRODUCTS
(THERMAL, UNLESS OTHERWISE SPECIFIED): CO, CO₂

CONDITIONS CONTRIBUTING TO
HAZARDOUS POLYMERIZATION: None

SECTION VI. SPILL OR LEAK PROCEDURES

PROCEDURES IF MATERIAL IS SPILLED:

Remove sources of heat or ignition, provide adequate ventilation, contain the leak. Absorb small spills with suitable material such as rags, straw or sand. Report spills as required to appropriate authorities.

WASTE DISPOSAL:

It is the responsibility of the user to determine if the material is a hazardous waste at the time of disposal. Please check before disposing of product or container to be sure you are in compliance with all applicable laws and regulations.

PROTECTIVE MEASURES DURING REPAIR AND MAINTENANCE OF CONTAMINATED EQUIPMENT:

Refer to Section VIII - Special Protection Information.

Avoid prolonged contact with used oil, wash skin thoroughly with soap and water.

SECTION VIII SPECIAL PROTECTION INFORMATION

VENTILATION REQUIREMENT: Ventilation is required when work place exposures exceed TLV.

PERMITTED THRESHOLD:	Agency: OSHA	OSHA	ACGIH	ACGIH	
AIR CONCENTRATIONS:	Year:	1972	1985	1985-86	1985-86
	Type:	TWA	PEL	TWA	STEL
	ppm:	-	-	-	-
	mg/m ³	5	5	5	10

SPECIFIC PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY: Normally none required. If high vapor or mist concentrations expected - use respirator approved for organic vapors and mists.

EYES: Safety goggles, or chemical splash goggles if splashing is anticipated.

DERMAL: Oil impervious gloves if frequent or prolonged contact is expected.

CLOTHING/EQUIPMENT: Wear body-covering work clothes to avoid prolonged or repeated exposure. Launder soiled work clothes before reuse.

SECTION IX TRANSPORTATION AND SPECIAL PRECAUTIONS

HAZARDOUS MATERIAL PLACARD/LABEL: None

STORAGE: Store below 150°F. Do not apply high heat or flame to container. Keep separate from strong oxidizing agents.

DOT INFORMATION:

DOT/UN Shipping Name:	Petroleum Lubricating Oil.
DOT Hazard Class:	Non-Hazardous
DOT/UN Hazard Identification #:	None assigned
DOT Shipping Container Restrictions:	None
DOT Placard:	None

CAUTION: Empty containers may contain product residue which could include flammable or explosive vapors.

Consult appropriate Federal, State and Local authorities before reusing, reconditioning, reclaiming, recycling or disposing of empty containers and/or waste residues of this product.

LABEL: Non-Hazardous. (OHCS)

All statements, information, and data provided in this material safety data sheet are believed to be accurate and reliable, but are presented without guarantee, warranty, or responsibility of any kind, expressed or implied, on our part. Users should make their own investigation to determine the suitability of the information or products for their particular purpose. Nothing contained herein is intended as permission, inducement or recommendation to violate any laws or to practice any invention covered by existing patents.