

HYVAC[®] PRODUCTS, INC.

MAIL: P.O. BOX 389 • PHOENIXVILLE, PA • 19460-0389 • U.S.A.

PLANT: 201 NORTH 5TH AVENUE • ROYERSFORD, PA • 19468 • U.S.A.

610-792-0500 PHN • 610-792-0600 FAX

EMAIL jeff@hyvac.com

INTERNET [HTTP://WWW.HYVAC.COM](http://WWW.HYVAC.COM)

HYVAC[®] Belt Drive High Vacuum Pumps

These five mechanical high vacuum pumps are older style belt drive vacuum pumps. They incorporate two-stage design, with the basic oil sealed rotary vane principle. They are excellent general purpose or roughing pumps capable of vacuum pressures to 1×10^{-4} Torr or .1 micron with fast recovery times. Since they are belt drive pumps, they offer excellent durability and resistance to contaminants.

The HYVAC vacuum pumps are equipped with a gas ballast valve, which helps purify the oil of condensable vapors and limit corrosion. The pumps use the standard NPT fittings on both intake and exhaust ports to allow for quick connection/disconnection to vacuum systems and for easy adaptation of optional equipment. The pumps are supplied with a charge of oil and an extra quart of HYVAC Pump Oil. The pumps have a drain cock for ease in changing oil and can be equipped for external oil filtration systems.

The HYVAC pumps are designed with an easily viewed, oil level sight glass, OSHA approved belt guard, capacitor start motors, on/off switch, electrical cord, and a sturdy base with bolt holes for mounting or installation of vibration isolators. The pumps come standard with HYVACS' one-year parts and labor guarantee assuring complete customer satisfaction.



HYVAC[®] PRODUCTS, INC.

P. O. Box 389 · PHOENIXVILLE · PA · 19460-0389

PHONE (610) 792-0500 · FAX (610) 792-0600

<http://www.hyvac.com>

1-800-628-0850

2-Stage Belt Drive Vacuum Pumps HyVac 2 - 45

	HYVAC 2	HYVAC 7	HYVAC 14	HYVAC 28	HYVAC 45
CATALOG #	91305	91506	91705	91905	91955
NUMBER OF STAGES:	2	2	2	2	2
FREE AIR DISPLACEMENT: (Liters/min.) (cfm)	25 .9	79 2.8	160 5.6	310 10.6	500 17.7
GUARANTEED ULTIMATE: PRESSURE (millitorr) PUMP SPEED (rpm) MOTOR (hp)	0.5 580 1/4	0.5 525 1/2	0.5 525 3/4	0.5 525 1	0.5 550 1 1/2
WEIGHT: (lbs.) (kg)	39 18	72 33	94 43	119 54	160 73
DIMENSIONS: (inches) (length) (width) (height)	15" 10" 11"	13" 11 1/2" 17 1/4"	15 3/4" 12 3/4" 17 7/8"	18 1/4" 15 1/2" 18"	19 1/2" 19 1/4" 21"
OIL CAPACITY:	1 Qt.	1 1/2 Qt.	2 1/2 Qt.	3 1/2 Qt.	4 1/2 Qt.
INTAKE NIPPLE (OD) (inches)	9/16"	7/8"	1 1/4"	1 5/16"	1 3/16"

For More Information Contact HyVAC Products **1-800-628-0850**.